

ISO general purpose metric screw threads — Tolerances —

Part 5: Limits of sizes for internal screw threads to mate with hot-dip galvanized external screw threads with maximum size of tolerance position h before galvanizing

ICS 21.040.10

National foreword

This British Standard reproduces verbatim ISO 965-5:1998 and implements it as the UK national standard.

The UK participation in its preparation was entrusted by Technical Committee FME/9, Bolts, nuts and accessories, to Subcommittee FME/9/3, Reference standards for fasteners, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this subcommittee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the ISO title page, pages ii to iv, pages 1 to 4 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

Amendments issued since publication

Amd. No.	Date	Comments

This British Standard, having been prepared under the direction of the Engineering Sector Committee, was published under the authority of the Standards Committee and comes into effect on 15 April 1999

© BSI 03-2000

ISBN 0 580 32355 2

Contents

	Page
National foreword	Inside front cover
Foreword	iii
Text of ISO 965-5	1

INTERNATIONAL
STANDARD

ISO
965-5

First edition
1998-12-15

**ISO general purpose metric screw
threads — Tolerances —**

Part 5:

Limits of sizes for internal screw threads to
mate with hot-dip galvanized external screw
threads with maximum size of tolerance
position h before galvanizing

Filetages métriques ISO pour usages généraux — Tolérances —

*Partie 5: Dimensions limites pour filetages intérieurs pour assemblages
avec des filetages extérieurs galvanisés à chaud de position de tolérance
maximale h avant galvanisation*



Reference number
ISO 965-5:1998(E)

Contents

	Page
Foreword	iii
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Designation	1
5 Deviations	1
6 Limits of sizes — Internal screw threads — Coarse thread series	2
Table 1 — Deviations	2
Table 2 — Internal screw thread limits for tolerance class 6AZ	3
Table 3 — Internal screw thread limits for tolerance class 6AX	4

Descriptors: Screw threads, ISO metric threads, hot-dip galvanizing, internal threads, dimensions, dimensional tolerances, dimensional deviations, designation.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 965-5 was prepared by Technical Committee ISO/TC 1, *Screw threads*, Subcommittee SC 2, *Tolerances*.

ISO 965 consists of the following parts, under the general title *ISO general purpose metric screw threads — Tolerances*

- *Part 1: Principles and basic data;*
- *Part 2: Limits of sizes for general purpose bolt and nut threads — Medium quality;*
- *Part 3: Deviations for constructional screw threads;*
- *Part 4: Limits of sizes for hot-dip galvanized external threads to mate with internal threads tapped with tolerance position H or G after galvanizing;*
- *Part 5: Limits of sizes for internal screw threads to mate with hot-dip galvanized external screw threads with maximum size of tolerance position h before galvanizing.*

1 Scope

This part of ISO 965 specifies deviations and limits of sizes for pitch and crest diameters for ISO general purpose metric internal screw threads conforming to ISO 262 having basic profile according to ISO 68-1.

Internal screw threads according to this part of ISO 965 are intended to mate with external screw threads with maximum size of tolerance position *h* before hot-dip galvanizing.

The limits of sizes for the tolerance quality specified are derived from tolerances specified in ISO 965-1.

The fundamental deviations for internal screw threads with a tolerance position *AZ* have been calculated according to the following formula:

$$EI_{AZ} = + (300 + 20P)$$

where

EI is expressed in micrometres;

P is expressed in millimetres.

The fundamental deviations for internal screw threads with a tolerance position *AX* have been calculated according to the following formula:

$$EI_{AX} = + (220P - 20)$$

where

EI is expressed in micrometres;

P is expressed in millimetres.

Products made with thread tolerances according to this part of ISO 965 may show load failure when tested in accordance with ISO 898-2 without adjustment of the other mechanical properties.

Internal screw threads with thread tolerances according to this part of ISO 965 must not be mated with external screw threads having thread tolerances according to ISO 965-4 because such combinations will create severe risk of thread stripping.

NOTE Internal screw threads with tolerance class 6AZ are primarily intended to mate with external screw threads centrifuged after hot-dip galvanizing.

Internal screw threads with tolerance class 6AX are primarily intended to mate with hot-dip galvanized external screw threads with heavy coating not centrifuged.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 965. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 965 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 68-1:1998, *ISO general purpose screw threads — Basic profile — Part 1: Metric screw threads*.

ISO 262:1998, *ISO general purpose metric screw threads — Selected sizes for screw, bolts and nuts*.

ISO 898-2:1992, *Mechanical properties of fasteners — Part 2: Nuts with specified proof load values — Coarse thread*.

ISO 965-1:1998, *ISO general purpose metric screw threads — Tolerances — Part 1: Principles and basic data*.

ISO 965-4:1998, *ISO general purpose metric screw threads — Tolerances — Part 4: Limits of sizes for hot-dip galvanized external screw threads to mate with internal screw threads tapped with tolerance position *H* or *G* after galvanizing*.

ISO 5408:1983, *Cylindrical screw threads — Vocabulary*.

3 Definitions

For the purpose of this part of ISO 965 the definitions given in ISO 5408 apply.

4 Designation

Tolerance designation for internal screw threads is

6AZ

or

6AX

Example:

M12 – 6AZ

or

M12 – 6AX

5 Deviations

The deviations for internal screw threads as specified in Table 1 are derived from the formulae for fundamental deviations below and from tolerances specified in ISO 965-1.

The fundamental deviations, EI_{AZ} and EI_{AX} , have been calculated according to the following formulae:

$$EI_{AZ} = + (300 + 20P)$$

and

$$EI_{AX} = + (220P - 20)$$

where

EI is expressed in micrometres;

P is expressed in millimetres

Table 1 — Deviations

Thread	Pitch <i>P</i> mm	Tolerance class	Internal thread			
			Pitch diameter		Minor diameter	
			<i>ES</i> μm	<i>EI</i> μm	<i>ES</i> μm	<i>EI</i> μm
M10	1,5	6AZ	+ 510	+ 330	+ 630	+ 330
		6AX	+ 490	+ 310	+ 610	+ 310
M12	1,75	6AZ	+ 535	+ 335	+ 670	+ 335
		6AX	+ 565	+ 365	+ 700	+ 365
M14, M16	2	6AZ	+ 552	+ 340	+ 715	+ 340
		6AX	+ 632	+ 420	+ 795	+ 420
M18, M20, M22	2,5	6AZ	+ 574	+ 350	+ 800	+ 350
		6AX	+ 754	+ 530	+ 980	+ 530
M24, M27	3	6AZ	+ 625	+ 360	+ 860	+ 360
		6AX	+ 905	+ 640	+ 1 140	+ 640
M30, M33	3,5	6AZ	+ 650	+ 370	+ 930	+ 370
		6AX	+ 1 030	+ 750	+ 1 310	+ 750
M36, M39	4	6AZ	+ 680	+ 380	+ 980	+ 380
		6AX	+ 1 160	+ 860	+ 1 460	+ 860
M42, M45	4,5	6AZ	+ 705	+ 390	+ 1 060	+ 390
		6AX	+ 1 285	+ 970	+ 1 640	+ 970
M48, M52	5	6AZ	+ 735	+ 400	+ 1 110	+ 400
		6AX	+ 1 415	+ 1 080	+ 1 790	+ 1 080
M56, M60	5,5	6AZ	+ 765	+ 410	+ 1 160	+ 410
		6AX	+ 1 545	+ 1 190	+ 1 940	+ 1 190
M64	6	6AZ	+ 795	+ 420	+ 1 220	+ 420
		6AX	+ 1 675	+ 1 300	+ 2 100	+ 1 300

6 Limits of sizes — Internal screw threads — Coarse thread series

Tolerance quality: medium

Thread engagement: normal

Tolerance classes: 6AZ and 6AX

Table 3 — Internal screw thread limits for tolerance class 6AX

Dimensions in millimetres

Thread	Length of thread engagement		Major diameter ^a min. ^b	Pitch diameter ^a		Minor diameter ^c	
	over	up to and including		max.	min.	max.	min.
M10	5	15	10,310	9,516	9,336	8,986	8,686
M12	6	18	12,365	11,428	11,228	10,806	10,471
M14	8	24	14,420	13,333	13,121	12,630	12,255
M16	8	24	16,420	15,333	15,121	14,630	14,255
M18	10	30	18,530	17,130	16,906	16,274	15,824
M20	10	30	20,530	19,130	18,906	18,274	17,824
M22	10	30	22,530	21,130	20,906	20,274	19,824
M24	12	36	24,640	22,956	22,691	21,892	21,392
M27	12	36	27,640	25,956	25,691	24,892	24,392
M30	15	45	30,750	28,757	28,477	27,521	26,961
M33	15	45	33,750	31,757	31,477	30,521	29,961
M36	18	53	36,860	34,562	34,262	33,130	32,530
M39	18	53	39,860	37,562	37,262	36,130	35,530
M42	21	63	42,970	40,362	40,047	38,769	38,099
M45	21	63	45,970	43,362	43,047	41,769	41,099
M48	24	71	49,080	46,167	45,832	44,377	43,667
M52	24	71	53,080	50,167	49,832	48,377	47,667
M56	28	85	57,190	53,973	53,618	51,986	51,236
M60	28	85	61,190	57,973	57,618	55,986	55,236
M64	32	95	65,300	61,778	61,403	59,605	58,805

^a Dimensions apply to internal screw threads after galvanizing and tapping oversize.^b Refers to the imaginary coaxial cylinder through the points where the requirement with regard to straightness of flank ceases.^c Dimensions apply to internal screw threads before galvanizing or after galvanizing and removal of zinc fragments.

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: 020 8996 9000. Fax: 020 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: 020 8996 9001. Fax: 020 8996 7001.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: 020 8996 7111. Fax: 020 8996 7048.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: 020 8996 7002. Fax: 020 8996 7001.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

If permission is granted, the terms may include royalty payments or a licensing agreement. Details and advice can be obtained from the Copyright Manager. Tel: 020 8996 7070.